

130 A1 SG

Access 2 - way kit

Painted DIN chassis, 20% glass fiber filled ABS material
Strong rigid chassis, non-magnetic, nonresonant

All weather woven glass fiber cone
Dynamic bass and precise midrange, humidity-resistant cone

Adjustable tweeter level
Tweeter level control according to location

Phase plug
Midrange control out of the listening axis

Air core inductors
Insensitive to parasite interferences

25mm (1") voice coil
High power handling

85mm (3-1/3") magnet
High sensitivity

Voice coil cooling system
Reliability, performance consistency

Aluminum inverted dome tweeter
Accurate treble

20mm (13/16") ferrofluid voice coil
Excellent power handling

Technical characteristics:

130mm (5") woofer
25mm (1") voice coil
85mm (3-1/3") magnet
Aluminum inverted dome tweeter
12/12dB/octave (5kHz) separated crossover
Adjustable tweeter level (3 level settings)
Max. power: 100W - Nom. power: 50W
Sensitivity (2.8V/1m): 91dB
Frequency response : 65Hz - 20kHz
Accessories : flush mounting and surface mounting supports provided (tweeter)

It makes the difference:

- Extremely dynamic sound
- Large soundstage
- Punchy bass and accurate treble
- The Focal sound

