

165 KR2

2-way K2 Power kit

- K2 composite sandwich cone

Impact and details

- Zamak chassis

Strong, rigid and non-magnetic chassis

- Butyl surround

Excellent reliability

- Engraved serial number
Certificate of authenticity

Better directivity of the mid-range

- Aluminum phase plug
- Heavy ferrite
Magnetic flux increase

- Adjustable tweeter level per stage of 3dB

Installation flexibility

- Polypropylene capacitor

Neutral reproduction of high frequencies

- Multi-wire air core inductor

Resistant to parasites, maximum dynamic



- TNK inverted dome tweeter

Smoothness and precision

- Neodymium ring magnet

Very high linearity and dynamism

- Foam surround

Extended frequency response

Technical characteristics :

165mm (6.5") Woofer

32mm (1.26") Voice coil

90mm (3.54") Magnet

TNK tweeter

Kevlar inverted dome

Separate crossover : 12/12/18dB/oct (4kHz)

Adjustable tweeter level: (0,-3,-6dB)

Max. power: 160W

Nom. power: 80W

Sensitivity (2,8V/1m): 93dB

Frequency response: 70Hz – 20kHz

Accessories: grilles supplied

It makes the difference:

- Treble smoothness
- Dynamic and neutrality
- Precision of sound stage
- Tweeter sound level adjustment
- Excellent linearity of the two speakers
- High sensitivity
- 2 Ohms impedance

