

100 VRS

Polyglass kit

- Polyglass cone
Neutral sound without coloration
- Butyl surround
Resilient material, promoting long life
- 25mm Kapton® voice-coil former
High power handling
- Zamak chassis
Strong rigid and non-magnetic chassis
- Neodymium magnet
Shallow woofer, easy installation
- Voice-coil cooling system
Optimum reliability, performance consistency
- Engraved serial number
Certificate of authenticity
- Adjustable tweeter level
Level setting according to tweeter slot
- Air core inductor with a low serial resistance
Insensitive to parasite
- Real 12/12 dB/octave crossover
Optimum coupling of woofer and tweeter
- Polypropylène capacitor
Neutral reproduction of high frequencies



- TNB inverted dome tweeter
Detailed and non directive
- Double push-pull Neodymium magnet
High linear tweeter
- Voice coil on aluminium former
High dissipation characteristics

Technical characteristics:

100mm (4") woofer
25mm (0.98") voice-coil
Neodymium magnet
45mm (1.77") tweeter
Inverted TNB dome
2 way separate crossover 12/12dB (5.9kHz)
Adjustable tweeter level: 0, -3, -6dB
Max. power: 80W
Nom. power: 40W
Sensitivity (2.83V/1m): 91dB
Frequency response: 90Hz – 28kHz
Grilles supplied

It makes the difference:

- Easy mounting, shallow woofer (1.56" – 39.5mm)
- An outstanding musicality in this price level
- Kit dedicated to Hi-Power car audio, no amplifier needed
- All Focal technologies



FOCAL
the Spirit of Sound