

ELECTRA 1007 S

Product specification sheet

Aluminum/Magnesium tweeter.
Very wide response from 2.5kHz to 30kHz.

6 1/2" (165mm) "W" cone mid-bass.
Patented composite sandwich.
Outstanding stiffness and lightness.

Body in Black Silk.
Panels in wood veneering, varnish 4 coats.




OPC (Optimum Phase Crossover)
Perfect staging.
Focal binding posts offering high torque and excellent contact.

Advanced γ Structure.
Massive structure of 2" (50mm) thick MDF.
No diffraction effect nor vibration.

Rear laminar port.
No noise, no distortion.
Removable foam bung for bass level setting.



- 100% Focal loudspeakers and drive-units made in France
- High size/performance ratio for optimum integration
- Exclusive Focal technologies



> 24" (60cm) Standard Electra S 1007.1 stand,
Aluminum and Black Silk

Type	2-way vented bookshelf loudspeaker
Drivers	6 1/2" (16,5cm) "W" midbass 1" (25mm) Al/Mg inverted dome tweeter
Frequency response (+/-3dB)	46Hz - 30kHz
Low frequency point (-6dB)	41Hz
Sensitivity (2.83V/1m)	89dB
Nominal impedance	8 Ω
Minimum impedance	3.9 Ω
Crossover frequency	2500Hz
Recommended amplifier power	25 - 150W
Dimensions (HxWxD)	15 3/16 x 10 3/8 x 13 3/4" (385x264x350mm)
Net weight	30.8lbs (14kg)

*The Al/Mg tweeter perfectly suits the **Electra 1007 S** that seduces with its communicative energy and its mid-range/treble, sparkling with details. Like the **Electra 1007 Be**, the quality of the bass, which is technically identical, is impressive, even in rooms of large dimensions. That's a high range compact loudspeaker with an exceptional quality/price ratio.*

