

ELECTRA 1027 S

Product specification sheet



6 1/2" (16.5cm) "W" cone midrange.
Patented composite sandwich.
Outstanding dynamics,
lightness and definition.

Two 6 1/2" (16.5cm) "W" cone woofers.
Patented composite sandwich.
Outstanding stiffness and lightness.

OPC (Optimum Phase Crossover).
Perfect staging.
Focal binding posts offering high
torque and excellent contact.

Body in Black Silk.
Panels in wood veneering, varnish 4 coats.


Al/Mg inverted dome tweeter.
Very wide response from 2.5kHz to 30kHz.
High definition and dynamics.

Advanced γ Structure.
Massive structure of 2" (50mm) thick MDF.
No diffraction effect nor vibration.

Rear laminar port.
Removable foam bung
for bass level setting.
Supplied spikes and plastic feet.



- 100% Focal loudspeakers and drive-units made in France
- High size/performance ratio for optimum integration
- Exclusive Focal technologies



Type	3-way vented floor standing speaker
Drivers	Two 6 1/2" (16.5cm) "W" woofers. 6 1/2" (16.5cm) "W" midrange. 1" (25mm) Al/Mg inverted dome tweeter.
Frequency response (+/-3dB)	42Hz - 30kHz
Low frequency point (-6dB)	34Hz
Sensitivity (2.83V/1m)	91dB
Nominal impedance	8 Ω
Minimum impedance	3.5 Ω
Crossover frequency	300Hz / 2500Hz
Recommended amplifier power	40 - 300W
Dimensions (HxWxD)	41 3/8 x 10 3/8 x 13 3/4" [1 050 x 264 x 350mm]
Net weight	68.2lbs [31kg]

This elegant floorstander impresses by its outstanding bass power considering its moderate size. Its sharpness, its definition, its perfect balance between extreme bass and extreme treble will be appreciated on any music type, at a high or low sound level and make of the 1027 S the queen of versatility.

