

130 VRS

Polyglass kit

Butyl surround

Promoting long life

Shallow mounting (48.5mm / 1-15/16")

Easy integration in the most exiguous spaces

Polyglass cone

Neutral sound without coloration

Zamak basket

Strong rigid chassis, non magnetic, non resonant

32mm (1^{1/4}" voice coil on Kapton® former

High power handling

38 SH neodymium magnet

High magnetic field for a high sensitivity

Voice coil cooling system

Optimized reliability, no dynamic compression

Air core inductor with a low serial resistance

Insensitive to parasites, better sensitivity

Adjustable tweeter level

Tweeter level setting according to the positioning

Polypropylene/Aluminum capacitor

Natural reproduction of high frequencies



Aluminum/magnesium inverted dome TNB tweeter

Smooth and detailed treble, large and precise sound stage

Dual push-pull neodymium magnet

Excellent linearity of the tweeter

Voice coil on aluminum former

High dissipation characteristics

Technical characteristics :

130mm (5") woofer

32mm (1^{1/4}) voice coil

38 SH neodymium magnet

45mm (1^{3/4}") TNB tweeter

Aluminum/magnesium inverted dome tweeter

12-18dB/octave 2-way crossover (4kHz)

Adjustable tweeter level (0, -3, -6dB)

Max. power: 100W

Nom. power: 50W rms

Sensitivity (2.8V/1m): 91dB

Frequency response: 80Hz – 28kHz

Accessories: grilles provided

It makes the difference :

- Easy installation for all kind of vehicles (shallow mounting: 48,5mm / 1-15/16")
- Hi-Fi sound for an optimized realism
- Large and precise sound stage
- Important dynamic
- The essentially of the Focal sound

