

30 A1 DB

NBR surround
Resilient material,
promoting long life

All weather woven glass fiber cone
Dynamic bass, humidity resistant

Gasket supplied
No air leak, better chassis damping

65mm (2-9/16") dual voice coil,
4 layer
High power handling

Spider support
More excursion

2x4 Ohm dual voice coil
Connection adaptability to
an amplifier

Voice coil cooling system
No dynamic compression,
optimized reliability

145mm magnet
High sensitivity

Zamak chassis
Rigid, non magnetic,
non resonant

Rubber magnet cap
Protecting magnet from shocks
and corrosion



Technical characteristics:

12" (30cm) High Power Subwoofer
65mm (2-9/16"), 4 layer voice coil (2x4 Ω)
145mm (5-11/16") magnet
Max. power handling: 500W
Nominal power handling: 250W
Sensitivity (2.8V/1m): 91dB
Frequency response: 25Hz* - 500Hz
*Depends on load

It makes the difference:

- Extended response in bass frequencies without distortion
- Bass density
- Great musical versatility
- The most affordable Focal sound

	25 litres	35 litres	40 litres
Frequency response (-3dB)	44Hz	42Hz	41Hz
Boost	2dB at 80Hz	1dB at 75Hz	Flat
Load	Sealed	Sealed	Sealed

