

690 CVX

Polyglass 2-way coaxial kit

- Butyl surround
Resilient material, promoting long life

- Adjustable aluminum inverted dome tweeter
Detailed and non directive

- 12dB/octave audiophile crossover
Time saving during the installation, optimum sound quality

- Polyglass cone
Neutral sound without coloration

- Aluminum protection cover
Protects the crossover from shocks

- 30mm (1-3/16") voice coil on Kapton® support
High power handling

- 20% glass fiber filled ABS material basket
Strong rigid, non-magnetic and non-resonant chassis

- Polypropylene capacitor
Extremely natural sound

- Air core inductor with a low serial resistance
Impervious to parasite



Technical characteristics:

164x235mm (6x9") woofer
30mm (1-3/16") voice-coil
90mm (3-9/16") magnet
Adjustable tweeter,
aluminum inverted dome
Integrated crossover (12dB/octave)
Max. power: 160W
Nom. power: 80W
Sensitivity(2.8V/1m): 93dB
Frequency response: 50Hz – 20kHz
Accessories: grilles provided

It makes the difference:

- Boost the bass level in the passenger compartment and spread sound at the rear of the vehicle
- Real integrated audiophile 12dB/octave crossover
- Dynamics and neutrality
- Installation rapidity

