

CHORUS 706 V

Product specification sheet

Aluminum/Magnesium inverted dome TNV tweeter.
Extended response to 28kHz.

6¹/₂" (165mm) Polyglass midbass.
Dynamic midrange, punchy bass.

Aerodynamic front port.
Low distortion



Solid MDF construction
up to 1" (25mm) width.
Non parallel inner wall structure.


OPC crossover.
Perfect staging.
New insulated Focal terminals.

> Chorus 706 V, Light Walnut finish.




- ◆ Speakers designed and manufactured by Focal.
- ◆ Exceptional sound and quality for the price.
- ◆ Light Walnut, Wengé, Black Ash finishes.

Other finishes available



Wengé



Black Ash



Optional 24" (60cm) S 700 V stand.

Type	2-way bass reflex bookshelf loudspeaker
Drivers	6 ¹ / ₂ " [165mm] Polyglass midbass 1" [25mm] TNV Al/Mg inverted dome tweeter
Frequency response [+/- 3dB]	55Hz- 28kHz
Low frequency point [- 6dB]	47Hz
Sensitivity [2.83V/1m]	90dB
Nom. impedance	8 Ohms
Minimum impedance	3.6 Ohms
Recommended amplifier power	25 - 120W
Crossover frequency	3000Hz
Dimensions [HxWxD]	15 ³ / ₈ x8 ³ / ₄ x11 ⁹ / ₁₆ " [390 x 222 x 293mm]
Net weight	18lb [8.2kg]

Chorus 706 V is the epitome of a reference, compact loudspeaker: a true Focal tradition. Superbly balanced and neutral, its accuracy and definition are ideal for rooms near 20m² without a drop in perceived volume.



FOCAL
the Spirit of Sound