CHORUS SR 800 V

Product specification sheet



Acrylic body, black miror effect.

Exclusive finish.

Polyfix wall mount system. Easy mounting.

Solid MDF construction.

Non parallel inner wall structure.













- ◆ High-end design, affordable luxury
- ◆ Speakers designed and manufactured by Focal

◆ A sound quality never seen before at this price level ◆ Acrylic body, 2 side finishes; Ebony and Natural

Туре	2-way sealed bipolar effects loudspeaker, Polyfix™ wall bracket
Drivers	2x5" (130mm) Polyglass mid-bass 2x1" (25mm) TNV Al/Mg inverted dome tweeter
Frequency response (+/- 3dB)	75Hz - 28kHz
Low frequency point (- 6dB)	65Hz
Sensitivity (2.83V/1m)	90dB
Nom. impedance	8 ohms
Minimum impedance (@25°C)	3.7 ohms @ 210Hz
Max. power handling.	120W
Power RMS	80W
Crossover frequency	3kHz
Dimensions (HxWxD)	11 ^{7/16°} x15 ^{3/4} "x6 ^{7/8} " (290x400x175mm)
Net weight	12.3lbs (5.6kg)

The capacity of the Chorus SR 800 V to fill surround space with precision is spectacular. Its behavior is optimized thanks to the integrated "Wall Boost Control" and with a exacting directivity. Compact, discrete, but Chorus in its spirit with an acrylic finish.



