

# 130 CA1 SG

Access coaxial kit

Painted DIN chassis, 20% glass fiber filled ABS material  
Strong rigid chassis, non-magnetic, non-resonant

Butyl surround  
Resilient material, promoting long life

Aluminum inverted dome, adjustable tweeter  
Accuracy, sound staging optimization

20mm (13/16") ferrofluid voice coil  
Excellent power handling

All weather woven glass fiber cone  
Dynamic bass and precise midrange, humidity-resistant cone

Aluminum inverted dome  
Excellent spatialization

85mm (3-1/3") magnet  
High sensitivity

25mm (1") voice coil  
High power handling

Built-in crossover (4.7 kHz)  
Easy and quick installation

Voice coil cooling system  
Reliability, performance consistency

## Technical characteristics:

130mm (5-1/8") woofer  
25mm (1") voice coil  
85mm (3-1/3") magnet  
Aluminum inverted dome tweeter  
6dB/octave built-in crossover  
Max. power: 120W - Nom. power: 50W  
Sensitivity (2.8V/1m): 91dB  
Frequency response: 65Hz - 20kHz

## It makes the difference:

- Direct wiring to a High Power car radio
- Large soundstage
- High power handling
- Bass quality and extremely dynamic sound
- The Focal sound

