

PROFILE 928



Features

- **3-way** bass-reflex floor standing loudspeaker ;
- Sophisticated **design** for maximum performance and aesthetic integration capability ;
- Bended, **multi-fold MDF** cabinet for toughness and optimal damping ;
- New **aluminum/magnesium alloy inverted dome** tweeter, Poron surround, frequency response up to 30 kHz, SACD and DVD-Audio compatibility ;
- **New generation** woofers and midrange composite **W sandwich cones** ;
- **OPC** filtering for perfect phase alignment and optimal directionality ;
- **Three finishing**, natural wood veneering.

Technical specifications

Type	3-way bass-reflex floor standing loudspeaker
Drivers	1" Al/Mg inverted dome tweeter 6-1/2" W cone midrange Two 6-1/2" W cone woofers
Frequency response (+/-3dB)	38 to 30.5kHz
Sensitivity (2,83V/1m)	91dB
Nom. impedance	8Ω
Min. impedance	3Ω at 150Hz
Max.power handling	200Watts
Crossover frequency	300/2600Hz
Dimensions (HxWxD)	41 ⁹ / ₈ "x90 ¹ / ₂ "x44 ¹ / ₈ " (1066x230x353mm)
Net weight	49.1lbs (22.3kg)



Focal® is a trademark of Focal-JMLab®