



Features

- 6" 2-way reference system
- Pure Beryllium inverted dome tweeter
- W sandwich composite woofer cone
- Crossblock parametric crossover
- Compact woofer with damping
- Ready for biwiring

Technical data

Туре	2 way, 6 ^{1/2} " (16.5cm) "W" woofer, 1" (2.5cm) Beryllium tweeter
Frequency response	66Hz to 40kHz
Sensitivity (2.83V/1M)	91.5dB
Power handling	100W
Nominale impedance	4 ohms
Voice-coil diameter	1 ^{1/2} " (40mm)
Voice-coil height	5/8" (15mm)
Xmax	3/16" (4.5mm)
Crossblock dim. (LxHxP)	13"x2 ^{1/4} "x10 ^{3/8} " (332x58x263mm)

*This system is also available as N°6 Active version (without Crossblock filter).



Focal[®] is a trademark of Focal-JMlab[®]

BP 374 - 108, rue de l'Avenir - 42353 La Talaudière cedex - Tel. 33 00 4 77 43 57 00 - Fax 33 00 4 77 37 65 87 - www.focal-fr.com Exact product details likely to change. Focal-Milab reserve the right to modify the specification, technology and price of the products without notice. Items may vary from those shown in the photographs. - © FocalJMlab - SCFR 041123/1