Cub² Sib & Co line





Key points

- Amplified bass enclosure (150W)
- Optimum coupling with Sib-T and Sib XL-T speakers
- Quick installation and connections
- RCA analog inputs for an audio source connection
- Adjustable active filter
 High energy 8^{1/4}" (21cm) woofer

Technical specifications

Frequency response	40Hz - 150Hz
Speaker	Polyflex® 8 ^{1/4} " (21cm) cone
Amplification	BASH® 150W rms
Filtering	Adjustable active filter from 50Hz to 150Hz
Connection	High and low level inputs and LFE input on RCA
Phase	0°/180° selector
Power supply	Autopower
Dimensions (H x L x D)	$13^{1/8} x 11^{13/16} x 11^{13/16}" (333 x 300 x 300 mm)$
Weight	24.3lb (11kg)



The invisible great Focal sound.

The Focal Professional Commercial Integration range is the answer to two fundamental constraints:

offering very high quality sound audio solutions
 promoting product integration to preserve architectural harmony.

Applications:

The Cub² amplified bass enclosure is the perfect complement to Sib-T and Sib XL-T. It offers an important extra bass as well as a stereo amplifier to supply the Sib-T and Sib XL-T loudspeakers. Its design permits an easy installation under a platform and can also be placed in a room corner.

Packaging

1 Cub² amplified bass enclosure 1 sound level remote control

Environmental characteristics

Ambient temperature Watertightness -25 °C to + 55 °C Dampenvironment

Installation synoptic

