

LITTLE BIRD® Specification sheet

Designation: Bird Little Black - Bird Little White / Reference: Black E0304 - White E0301



Available in Diamond Black and Diamond White finishes



- A true 2-way ultra compact hifi loudspeaker
- Impressive sound power/dimension ratio with true bass frequencies
- Wall, ceiling or table mounting
- Flexible “Cocotte” and “Tulipe” stands with integrated cable route
- Fire and UV proof ABS body
- Optional floor stand

	Little Bird
Type	Ultra compact 2-way sealed speaker
Drivers	4" [10cm] Polyflex cone midbass Aluminum dome tweeter
Frequency response (±3dB)	89Hz – 25kHz
Low frequency point (-6dB)	81Hz
Sensitivity (2.83V/1m)	87dB
Nominal impedance	8 Ohms
Minimum impedance	3.5 Ohms
Crossover frequency	2500Hz
Recommended amplifier power	15 – 75W
Dimensions (H x W x D)	Tulipe: 8x4 ^{12/16} x5 ^{1/8} " (202 x 119 x 130mm) Cocotte: 7 ^{11/16} x6 ^{1/4} x5 ^{13/16} " (195 x 159 x 147mm)
Weight	1.65lb (0.75kg)

The smallest of the Bird family and perhaps the most impressive: never such a compact loudspeaker has recreated such a sound! A sound that can become huge when Little Bird is combined with the Power Bird subwoofer/amplifier. Its innovative and sophisticated design enables a positioning on any support and rotation towards any chosen direction, very simply. Its minimalist dimensions make it a very unobtrusive and contemporary object.



FOCAL
the Spirit of Sound