

CHORUS OD 706 V

Product specification sheet

Jointed and notched fixing.

High damping box
ABS UV treated can be painted.

Punched aluminum grille.

OPC crossover.
Perfect staging.



Aluminum/Magnesium inverted dome TNV tweeter.
Extended response to 28kHz.
Anti-drop frame.

6¹/₂" (165mm) Polyglass mid-bass.
Dynamic medium, articulated bass.
All weather cone woofer.



- ♦ High performance, excellent size/efficiency ratio
- ♦ Speakers designed and manufactured by Focal
- ♦ A sound quality never before seen at this price level



Wall fixing on anti-vibration rubber foam

Type	2-way closed outdoor speaker
Drivers	6 ¹ / ₂ " (16.5cm) Polyglass mid-bass 1" (25mm) TNV Al/Mg inverted dome tweeter
Frequency response (+/- 3dB)	60Hz - 28kHz
Low frequency point [- 6dB]	52Hz
Sensitivity (2.83V/1m)	90dB
Nom. impedance	8 ohms
Minimum impedance	3.6 ohms
Crossover frequency	3 000Hz
Recommended amplifier power	25 - 150W
Dimensions (HxWxD)	11 ¹⁵ / ₁₆ "x8 ¹ / ₂ "x7 ⁹ / ₁₆ " (304x216x192mm)
Net weight	7lbs (3.2kg)

Bring the Focal sound to the outside is the vocation of the outdoor OD 706 V loudspeaker, waterproof and resistant to common weather conditions. Made on the model of the Chorus 706 V, with which it shares the drivers, the musical and technical performance is excellent, all this with a very compact size.



FOCAL
the Spirit of Sound