ELECTRA 1028 Be



Product Data Sheet

The Electra 1027 Be was a flagship of the Focal range, the 1028 Be goes even further, especially in the bass with the dual port Powerflow system. The dynamic leaps forward to be in harmony with the generosity and definition of the midrange-treble register that has always been a reference. A compact floorstander with irrefutable charm.

6^{1/2}" (16.5cm) 'W' cone midrange Patented composite sandwich Outstanding dynamics, lightness and definition

New pure Beryllium IAL (27mm) 1^{1/4}" tweeter Very wide response from 2kHz to 40kHz Low resonant frequency: 680Hz

Two 6^{1/2}" (16.5cm) 'W' cone woofers Patented composite sandwich Outstanding stiffness and lightness

> Front laminar port No noise, no distortion No dynamic compression



Body in metallic Slate Grey piano lacquer Panels in wood veneering, 11 coat varnish

Advanced γ Structure Massive structure up to 2" (50mm) thick MDF No diffraction effect nor vibration

OPC filtering
Perfect staging
Focal binding posts offering high
torque and excellent contact

Powerflow back port Increased efficiency and impact Removable foam bungs for bass setting





Black Lacquer

Ebene

Key points

- Made in France loudspeakers and drivers
- High size/performance ratio for optimum integration
- Powerflow port

Туре	3-way vented floor standing speaker, Powerflow
Drivers	Two $6^{1/2}$ " (16.5cm) 'W' woofers $6^{1/2}$ " (16.5cm) 'W' midrange $1^{1/4}$ " (27mm) pure Beryllium IAL inverted dome tweeter
Frequency response (+/-3dB)	34Hz - 40kHz
Low frequency point (-6dB)	28Hz
Sensitivity (2.83V/1m)	91.5dB
Nominal impedance	8Ω
Minimum impedance	3.5Ω
Crossover frequency	350Hz / 2,200Hz
Recommended amplifier power	40 - 300W
Dimensions (HxWxD)	43 ^{11/16} x10 ^{3/8} x13 ^{3/4} " (1,110x264x350mm)
Net weight	72.6lbs (33kg)

