ELECTRA 1038 Be



Product Data Sheet

As the whole Electra Be 2 line, the 1038 Be benefits from new components and settings. The awesome strength of the three 7" (18cm) woofers, endless power, is now added to the new qualities gained in terms of sound image and definition. A true weapon of mass seduction.

61/2" (165mm) 'W' cone midrange Patented composite sandwich Outstanding dynamics, lightness and definition

New pure Beryllium IAL (27mm) 1^{1/4}" tweeter Very wide response from 2kHz to 40kHz Low resonant frequency: 680Hz

Three 7" (18cm) 'W' cone woofers

Patented composite sandwich Outstanding stiffness and lightness

Body in metallic Slate Grey piano lacquer

Panels in wood veneering, varnish 11 coats




Advanced y Structure Massive structure up to 2" (50mm) thick MDF No diffraction effect nor vibration

OPC (Optimum Phase Crossover) Perfect staging Focal binding posts offering high torque and excellent contact

Front laminar port No noise, no distortion No dynamic compression





Black Lacquer

Ebene

Key points

- Made in France loudspeakers and drivers
- Very high power handling

Туре	3-way vented floor standing speaker
Drivers	Three 7" (18cm) "W" woofers 6 ^{1/2} " (16.5cm) "W" midrange 1 ^{1/4} " (27mm) pure Beryllium IAL inverted dome tweeter
Frequency response (+/-3dB)	33Hz - 40kHz
Low frequency point (-6dB)	26Hz
Sensitivity (2.83V/1m)	93dB
Nominal impedance	8Ω
Minimum impedance	3.3Ω
Crossover frequency	230Hz / 2,200Hz
Recommended amplifier power	40 - 400W
Dimensions (HxWxD)	49 ^{3/16} x11 ^{15/16} x15 ^{3/4} " (1,250x303x400mm)
Net weight	112.2lbs (51kg)

