

# DIRECT FET® AMPLIFIER

## FDS 2.350

Ultra-compact 2 channel amplifier

- Aluminium chassis  
high heat dissipation



- Hidden connectors  
Stackable chassis  
Built-in active crossovers

- D Class amplification  
Optimal integration Direct FET® Technology

## KEY POINTS

- D Class – Direct Fet® Technology - Efficient heat dissipation and precision
- Stable under 2 Ohms
- Stackable aluminium chassis with high heat dissipation
- Low noise operational amplifiers New Japan Radio® NJM4580
- Low ESR capacitors - 105°C (220°F)
- Pseudo-balanced inputs



## TECHNICAL SPECIFICATIONS

**Stereo D Class bridgeable amplifier**  
**CEA power (4 Ohms):** 2x105 Watts RMS  
**Power max (2 Ohms):** 2x170 Watts RMS

**Power max (4 Ohms bridged):** 1x360 Watts RMS  
**Configurable high-pass/low-pass crossover:** 40Hz-400Hz  
**Full range mode**  
**Bass boost (0-12dB)**  
**Protections:** Short circuit / low impedance / polarity reversal / DC / power drop / over heating protection

**Dimensions (LxHxW):**  
7<sup>13/16</sup>x4<sup>1/4</sup>x1<sup>11/16</sup> (199x108x43mm)  
**Weight:** 1.9 lbs

 **Performance**  
CREATE YOUR SOUND

 **FOCAL**  
THE SPIRIT OF SOUND