KANTA CENTER



Product data sheet

Kanta Center is the center channel speaker of the line. The ideal complement to a multi-channel Kanta system, it provides an identical level of performance at low and very high SPL, making it an excellent match for both the floorstanding speakers and the bookshelf speaker of the line. In parallel, definition in the midrange and high frequencies and its tonal balance were the focus of particular attention during development. The remarkable neutrality lends itself to thrilling emotion for an unparalleled Home Theater experience.



Key points

- Combines performance and compactness
- Remarkable tonal balance in the midrange and high frequencies for a highly realistic vocals
- Transducers integrating Focal's latest technologies
- Speaker drivers developed and manufactured in France
- Optional stand for optimal integration
- Numerous standard finishes

| Туре | 2-way bass-reflex center speaker |
|------------------------------------|---|
| Drivers | 2 x 6 ^{1/2} " (16.5cm) Flax bass-midrange with TMD® suspension and NIC motor 1 ^{1/16} " (27mm) "IAL3" pure Beryllium inverted dome tweeter |
| Sensitivity (2,83V/1m) | 91dB |
| Frequency Response (+/-3dB) | 55Hz - 40kHz |
| Low Frequency Point (- 6dB) | 50Hz |
| Nominal Impedance | 8Ω |
| Minimum Impedance | 3.5Ω |
| Recommended Amplifier Power | 40-200W |
| Crossover Frequency | 2,400Hz |
| Dimensions (HxWxD) | 9 ^{11/16} x 22 ^{3/32} x 15 ^{15/32} " (24.6 x 56.1 x 39.3cm) |
| Net weight (with front grille) | 39.1lbs (18kg) |
| Packaging dimensions (HxWxD) | 15 ^{3/4} x 26 ^{3/8} x 20 ^{15/32} " (40 x 67 x 52cm) |
| Total weight (including packaging) | 46.4lbs (21kg) |



