

Integration 130 VRS



2-way kit

- Butyl surround
- Promoting long life**
- Shallow mounting (1 15/16"/48.5mm)
- Easy integration in the most exiguous spaces**
- Polyglass cone
- Neutral sound without coloration**



- Zamak basket
- Strong rigid chassis, non magnetic, non resonant**
- 1 1/4" (32mm) voice coil on Kapton® former
- High power handling**
- N38 neodymium magnet
- High magnetic field for a high sensitivity**
- Voice coil cooling system
- Optimized reliability, no dynamic compression**

- Air core inductors with a low serial resistance
- Insensitive to parasites, better sensitivity**
- Adjustable tweeter level
- Tweeter level setting according to the positioning**
- Polypropylene/Aluminum capacitor
- Natural reproduction of high frequencies**

- Aluminum/magnesium inverted dome TNB tweeter
- Smooth and detailed treble, large and precise sound stage**
- Dual push-pull neodymium magnet
- Excellent linearity of the tweeter**
- Voice coil on aluminum former
- High dissipation characteristics**

ADVANTAGES

- Easy installation for all kind of vehicles (shallow mounting: 1 15/16" / 48.5mm)
- Hi-Fi sound for an optimized realism
- Large and precise sound stage
- The essentials of Focal sound

TECHNICAL CHARACTERISTICS

Woofer: 5" (130mm)
Voice-coil: 1 1/4" (32mm)
Neodymium magnet: N38
TNB tweeter: 1 3/4" (45mm)
Aluminum/magnesium inverted dome tweeter

2-way component crossover: 12/18dB/oct. (4kHz)
Adjustable tweeter level: (0, -3, -6dB)
Max. power: 100W
Nom. power: 50W rms

Sensitivity (2.83V/1m): 91dB
Frequency response: 80Hz – 28kHz
Accessories: supplied grilles