


CUSTOM IW 106

Product specification sheet

Aluminum grille
Can be painted



Reinforced white ABS chassis
- Very low vibration
- Can be painted.

Adjustable tweeter level
Adjustable from -3 dB to +3 dB




Aluminum inverted dome swivel tweeter
- Extended response to 20kHz
- Low directivity

6-1/2" (165mm) Fiberglass woofers
High power handling


FEATURES

- 100 % **Focal technologies.**
- **High power** handling.
- **Easy integration.**
- **Wall cut-out** template supplied.
- **Paint mask** supplied.
- Autoreset **polyswitch** fuse.
- **Splashproof**, design to work in **wet environment.**
- **The Focal sound.**



Wall bracket mounting
Quick and easy mounting

Type	In-wall speaker
Speakers	6-1/2" (165mm) fiberglass cone midbass 1" (25mm) aluminum inverted dome tweeter
Frequency response (+/-3dB)	60Hz - 20kHz
Sensitivity (2,83V/1m)	89dB
Nom. impedance	8Ω
Protection	Autoreset Polyswitch fuse
Max. power	120 Watts
Tweeter ajustement	-3dB/ 0dB/ +3dB
Crossover frequency	3300Hz
Frame size	(L) 8-1/8" x (H) 12-3/16" (207 x 310mm)
Cut-out dimensions (HxW)	(L) 6-11/16" x (H) 10-5/8" (170 x 273mm)
Depth from wall	2-13/16" (71mm)
Net weight	3.4lbs (1.6kg)



FOCAL
the spirit of sound