CUSTOM OD 108

Product specification sheet

Aluminum inverted dome tweeter.

Bass-reflex port.
Deep and punchy bass.

8" (21cm) midbass. Glassfiber cone. High power handling.



Jointed and notched fixing.

ABS box. Non-parallel sides. Protection against UV rays.

OPC crossover.
Optimum phase control.











Aluminum protection grille

- ◆ High power, long-range outdoor loudspeaker
- Great adaptability
- ◆The Focal sound, excellent quality

Туре	2-way bass-reflex outdoor speaker
Drivers	8" (21cm) fiberglass midbass 1" (25mm) Aluminum inverted dome tweeter
Frequency response (+/- 3dB)	50Hz - 20kHz
Low frequency point (- 6dB)	42Hz
Sensitivity (2.83V/1m)	91dB
Nom. impedance	8 ohms
Minimum impedance	6.5 ohms
Crossover frequency	2 400Hz
Recommended amplifer power	10 - 200W
Dimensions (HxWxD)	16 ^{5/16} x11 ^{5/16} x10 ^{3/16} "
	[414x287x258mm]
Net weight	12.8lbs (5.8kg)

The Custom 100 "big sound" can now be brought outside with the 0D 108 loudspeaker. Equipped with a 8" (21cm) glassfiber cone and an Aluminum inverted dome tweeter, this all-weather loudspeaker delivers a powerful sound with solid bass thanks to its high-efficiency and its high power-handling. Suitable in long-range situations (up to more than 30m) as well as in short-range, the 0D 108 is a versatile loudspeaker, able to perfectly work in low or high level.



