CAR AUDIO



Elite - Utopia Be
Ultima





Utopia Be

No limit for Passion!

A Unique sensation in the world, experience the Grande UTOPIA in your car.

ULTIMA is a full active car audio kit designed and inspired by all the best drivers used in our high-end loudspeakers.

A real midbass developed from the "Grande Utopia EM" midrange associated with its tweeter with IAL2 technology to drive a 2-way front component kit.

To be sure to have the best flat and neutral frequency response we associated two 8" subwoofers designed for our professional monitoring system SM9.

With a high air decompression from the Power Flower woofer, the distortion is reduced to the minimum and offers high dynamic.

Incredible materials and all the best Focal knowledge used on this kit are not the only highlights... more than a "product" it's a real complete full active hi-fi system... handmade in France passionately for car and music lovers.

From the low bass level to the very high frequencies, the listening pleasure is given by details, neutrality and high dynamic.





TW Ultima

Diameter: 215/16" (75mm)
Cone technology: Pure Beryllium inverted dome Magnet: Neodynium IAL2 motor
Max. power: 200W (with filtering)
Nom. power: 50W RMS (with filtering)
Sensitivity (2.83V/1m): 93dB
Impedance: 6 0hms

Frequency Response: 500Hz to 40kHz Suggested load volume: 0.01 cu ft (0.3L) in sealed enclosure



Full active ULTIMA kit in its wood Black Satin case Included authenticity certificate, service manual, FOCAL tool CD for settings.

Composition of the kit:

2 x Tweeters, 2 x Midbass, 2 x Subwoofers



6 W Ultima

Diameter: 6^{1/2}." (165mm)
Cone technology: Composite "W" sandwich cone
Voice coil diameter: 1 ¹⁷/16" (40mm)
Magnet: Power flower multi ferrite
Max. power: 240W
Nom. power: 120W RMS
Sensitivity (2.83V/1m): 90.5dB

Impedance: 4 Ohms Frequency Response: 60Hz to 4.5kHz

Suggested load volume: 1 cu ft (30L) in sealed enclosure



8 W Ultima

Diameter: 8" (200mm)

Cone technology: Composite "W" sandwich cone Voice coil: 1^{15/16}" (50mm) Magnet: Dual ferrite Max. power: 600W Nom. power: 300W RMS Sensitivity (2.83V/1m): 90.2dB Impedance: 6 0hms Frequency Response: 40Hz to 120Hz

Suggested load volume for 1 subwoofer: 0.79 cu ft (22.5L) in ported enclosure Port size suggested: 611/16" x Ø 23/8" – (17cm x Ø 6cm)























FOCAL® is a trademark of FOCAL-JMLAB®



Focal-JMlab® - BP 374 - 108, rue de l'Avenir - 42353 La Talaudière cedex - France Tel . +33 [0] 477 435 700 - Fax + 33 [0] 477 435 704 - © Focal-JMlab 2012 - SCAB-131125/1